

PAINTED STEEL BASE FIBERGLASS HOOD AERATION BLOWER PACKAGES

Aquapoint positive displacement blower systems mounted on welded steel bases provide exceptional stability and durability. Each steel blower base is outfitted with an integral discharge silencer for sound attenuation. The fiberglass enclosure provides exceptional weather protection and sound attenuation. The gel coat exterior is designed to resist ultraviolet degradation and will never crack, peel or require painting. A stainless steel support arm and locking hood allow for easy maintenance access. Choose from a variety of optional features to reduce noise, monitor component conditions and ensure efficient operation. Contact AquaPoint for application specific blower sizing and specifications.



STANDARD BLOWER PACKAGES

MODEL	BASE	BLOWER MODEL	MOTOR HP	DISCHARGE
APSBF-7.5	PD33-4	URAI-36	7.5	2.5"
APSBF-10	PD33-4	URAI-45	10	3"
APSBF-15	PD33-4	URAI-47	15	3"
APSBF-20	PD33-4	URAI-47	20	3"
APSBF-25	PD33-4	URAI-56	25	4"
APSB-30	PD33-4	URAI-56	30	4"

STANDARD FEATURES

- Painted Steel Base With Integral Discharge Silencer
- Roots URAI Dual-Lobe Blower Blocks
- Premium Efficient ODP Motors
- Adjustable Motor Base
- Intake Filter / Silencer
- Dual V-Belt Drive System
- Belt Guard
- Check Valve
- Pressure Relief Valve
- Flexible Discharge Connection
- Pressure Gauge

OPTIONAL FEATURES

- Tri-Lobe Blower Blocks for Sound Reduction
- Premium Efficient TEFC Motors
- Inlet Silencer
- Temperature Gauge
- Filter Gauge
- Pressure Shut Off Switch
- Integral VFD Controls

39 Tarkiln Place
New Bedford, MA 02745
T (508) 985-9050 | F (508) 985-9072

AQUAPOINT.COM